

Low Profile Capacitors

■ HOW TO ORDER

TT	31	X	225	M	100	C	T
Series	Size	Dielectric	Capacitance	Tolerance	Rated voltage	Termination	Packaging
TT=Low profile	21=0805 (2012) 31=1206 (3216) 32=1210 (3225)	X=X5R F=Y5V	Two significant digits followed by no. of zeros. And R is in place of decimal point. eg.: 225=22x10 ⁵ =2,200,000pF =2.2μF	K=±10% M=±20% Z=+20/-80%	Two significant digits followed by no. of zeros. And R is in place of decimal point. 6R3=6.3 VDC 100=10 VDC 160=16 VDC	C=Cu/Ni/Sn	B=Bulk T=7" reeled

■ PACKAGING DIMENSION AND QUANTITY

Size	Thickness Max (mm)/Symbol	7" reel	
		Paper tape	Plastic tape
0805 (2012)	0.95	T	4k
1206 (3216)	0.95	T	4k
	1.25	J	-
1210 (3225)	0.95	T	-

Unit: pieces

■ CAPACITANCE RANGE

Dielectric	Size	Capacitance	Tolerance	Rated Voltage (VDC)	Thickness Max (mm)	Part Number
X5R	0805	1.0μF	±10%, ±20%	10	0.95	TT21X105□100CT
		4.7μF	±10%, ±20%	6.3	0.95	TT21X475□6R3CT
	1206	2.2μF	±10%, ±20%	10	0.95	TT31X225□100CT
		3.3μF	±10%, ±20%	10	0.95	TT32X335□100CT
Y5V	0805	4.7μF	±10%, ±20%	10	0.95	TT32X475□100CT
		2.2μF	-20/+80%	16	0.95	TT21F225Z160CT
		3.3μF	-20/+80%	10	0.95	TT21F335Z100CT
		4.7μF	-20/+80%	10	0.95	TT21F475Z100CT
	1206	4.7μF	-20/+80%	16	0.95	TT31F475Z160CT
		10μF	-20/+80%	10	0.95	TT31F106Z100CT
		10μF	-20/+80%	16	1.25	TT31F106Z160CT
		10μF	-20/+80%	10	0.95	TT32F106Z100CT

 Please specify the capacitance tolerance code.

1. This series product is suited to reflow soldering process only.

2. For more information about products with special capacitance or other data, please contact WTC local representative.

Appendix I : Reliability Test Conditions and Requirements

NO.	Item	Test Condition	Requirements																																																																
1.	Visual and Mechanical	---	<ul style="list-style-type: none"> * No remarkable defect. * Dimensions to confirm to individual specification sheet. 																																																																
2.	Capacitance	Class I : NPO Cap 1000pF 1.0±0.2Vrms, 1MHz±10%	<ul style="list-style-type: none"> * Shall not exceed the limits given in the detailed spec. <p>NPO: Cap 30pF, Q 1000; Cap<30pF, Q 400+20C X7R, X5R:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td rowspan="2">50V</td> <td rowspan="2">2.5%</td> <td>3.0%</td> <td>All 0201:0603 0.047µF;0805 0.18µF; 1206 0.47µF</td> </tr> <tr> <td>7.0%</td> <td>0603 0.33µF;TT series & Cap 1µF</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">3.5%</td> <td>5.0%</td> <td>0805 1µF, 1210 10µF</td> </tr> <tr> <td>10%</td> <td>0603 0.33µF;0603 0.15µF; 0805 0.68µF;1206 2.2µF</td> </tr> <tr> <td>16V</td> <td>3.5%</td> <td>5.0%</td> <td>TT series & Cap 1µF</td> </tr> <tr> <td>10V</td> <td>5.0%</td> <td>10.0%</td> <td>TT series & Cap 1µF;0805 10µF</td> </tr> <tr> <td>6.3V</td> <td>10.0%</td> <td>15.0%</td> <td>0805 22µF;1210 100µF</td> </tr> </tbody> </table> <p>Y5V:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>5.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td rowspan="2">35V</td> <td rowspan="2">7.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td>---</td> <td>---</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">5.0%</td> <td>7.0%</td> <td>0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF</td> </tr> <tr> <td>9.0%</td> <td>0402 0.068µF</td> </tr> <tr> <td>16V (C<1.0µF)</td> <td>7.0%</td> <td>9.0%</td> <td>0402 0.068µF; 0603 0.68µF</td> </tr> <tr> <td>16V (C 1.0µF)</td> <td>9.0%</td> <td>12.5%</td> <td>0805 4.7µF;1206 10µF;1210 22µF</td> </tr> <tr> <td>10V</td> <td>12.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>6.3V</td> <td>20.0%</td> <td>---</td> <td>---</td> </tr> </tbody> </table>	Rated vol.	D.F.	Exception of D.F.		50V	2.5%	3.0%	All 0201:0603 0.047µF;0805 0.18µF; 1206 0.47µF	7.0%	0603 0.33µF;TT series & Cap 1µF	25V	3.5%	5.0%	0805 1µF, 1210 10µF	10%	0603 0.33µF;0603 0.15µF; 0805 0.68µF;1206 2.2µF	16V	3.5%	5.0%	TT series & Cap 1µF	10V	5.0%	10.0%	TT series & Cap 1µF;0805 10µF	6.3V	10.0%	15.0%	0805 22µF;1210 100µF	Rated vol.	D.F.	Exception of D.F.		50V	5.0%	---	---	35V	7.0%	---	---	---	---	25V	5.0%	7.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF	9.0%	0402 0.068µF	16V (C<1.0µF)	7.0%	9.0%	0402 0.068µF; 0603 0.68µF	16V (C 1.0µF)	9.0%	12.5%	0805 4.7µF;1206 10µF;1210 22µF	10V	12.5%	---	---	6.3V	20.0%	---	---
Rated vol.	D.F.	Exception of D.F.																																																																	
50V	2.5%	3.0%	All 0201:0603 0.047µF;0805 0.18µF; 1206 0.47µF																																																																
		7.0%	0603 0.33µF;TT series & Cap 1µF																																																																
25V	3.5%	5.0%	0805 1µF, 1210 10µF																																																																
		10%	0603 0.33µF;0603 0.15µF; 0805 0.68µF;1206 2.2µF																																																																
16V	3.5%	5.0%	TT series & Cap 1µF																																																																
10V	5.0%	10.0%	TT series & Cap 1µF;0805 10µF																																																																
6.3V	10.0%	15.0%	0805 22µF;1210 100µF																																																																
Rated vol.	D.F.	Exception of D.F.																																																																	
50V	5.0%	---	---																																																																
35V	7.0%	---	---																																																																
		---	---																																																																
25V	5.0%	7.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF																																																																
		9.0%	0402 0.068µF																																																																
16V (C<1.0µF)	7.0%	9.0%	0402 0.068µF; 0603 0.68µF																																																																
16V (C 1.0µF)	9.0%	12.5%	0805 4.7µF;1206 10µF;1210 22µF																																																																
10V	12.5%	---	---																																																																
6.3V	20.0%	---	---																																																																
3.	Q/ D.F. (Dissipation Factor)	Class II : X7R, X5R, Y5V Cap 10µF, 1.0±0.2Vrms, 1KHz±10% Cap>10µF, 0.5±0.2Vrms, 120Hz±20%																																																																	
4a.	Dielectric Strength	<ul style="list-style-type: none"> * To apply voltage (50V) 250%. * Duration : 1 to 5 sec. * Charge & discharge current less than 50mA. <table border="1"> <thead> <tr> <th>To apply voltage :</th> <th></th> </tr> </thead> <tbody> <tr> <td>100V</td> <td>3 times V DC</td> </tr> <tr> <td>200V ~ 300V</td> <td>2 times V DC</td> </tr> <tr> <td>500V ~ 999V</td> <td>1.5 times V DC</td> </tr> <tr> <td>1000V ~ 3000V</td> <td>1.2 times V DC</td> </tr> </tbody> </table> <ul style="list-style-type: none"> * Cut-off, set at 10mA * TEST= 15 sec. * RAMP=0 	To apply voltage :		100V	3 times V DC	200V ~ 300V	2 times V DC	500V ~ 999V	1.5 times V DC	1000V ~ 3000V	1.2 times V DC	<ul style="list-style-type: none"> * No evidence of damage or flash over during test. 																																																						
To apply voltage :																																																																			
100V	3 times V DC																																																																		
200V ~ 300V	2 times V DC																																																																		
500V ~ 999V	1.5 times V DC																																																																		
1000V ~ 3000V	1.2 times V DC																																																																		
4b.	Dielectric Strength (for X1/Y2 & X2/Y3)	<ul style="list-style-type: none"> * To apply 1500 VAC voltage. * Duration: 60 sec. 	<ul style="list-style-type: none"> * No evidence of damage or flash over during test. 																																																																
5.	Insulation Resistance	To apply rated voltage for max. 120 sec.	10G or RxC 500 -F whichever is smaller.																																																																
		Rated voltage: 100 ~ 500V To apply rated voltage for 60 sec.	10G																																																																
		Rated voltage: > 500V To apply 500V for 60 sec.	10G																																																																
6.	Temperature Coefficient	With no electrical load.																																																																	
		<table border="1"> <thead> <tr> <th>T.C.</th> <th>Operating Temp</th> </tr> </thead> <tbody> <tr> <td>NPO (COG)</td> <td>-55~125°C at 25°C</td> </tr> <tr> <td>NPO (COJ)</td> <td>-55~125°C at 25°C</td> </tr> <tr> <td>X7R</td> <td>-55~125°C at 25°C</td> </tr> <tr> <td>X5R</td> <td>-55~85°C at 25°C</td> </tr> <tr> <td>Y5V</td> <td>-25~85°C at 20°C</td> </tr> </tbody> </table>	T.C.	Operating Temp	NPO (COG)	-55~125°C at 25°C	NPO (COJ)	-55~125°C at 25°C	X7R	-55~125°C at 25°C	X5R	-55~85°C at 25°C	Y5V	-25~85°C at 20°C	<table border="1"> <thead> <tr> <th>T.C.</th> <th>Capacitance Change</th> </tr> </thead> <tbody> <tr> <td>NPO (COG)</td> <td>Within ±30ppm/°C</td> </tr> <tr> <td>NPO (COJ)</td> <td>Within ±120ppm/°C</td> </tr> <tr> <td>X7R</td> <td>Within ±15%</td> </tr> <tr> <td>X5R</td> <td>Within ±15%</td> </tr> <tr> <td>Y5V</td> <td>Within +30%/-80%</td> </tr> </tbody> </table>	T.C.	Capacitance Change	NPO (COG)	Within ±30ppm/°C	NPO (COJ)	Within ±120ppm/°C	X7R	Within ±15%	X5R	Within ±15%	Y5V	Within +30%/-80%																																								
T.C.	Operating Temp																																																																		
NPO (COG)	-55~125°C at 25°C																																																																		
NPO (COJ)	-55~125°C at 25°C																																																																		
X7R	-55~125°C at 25°C																																																																		
X5R	-55~85°C at 25°C																																																																		
Y5V	-25~85°C at 20°C																																																																		
T.C.	Capacitance Change																																																																		
NPO (COG)	Within ±30ppm/°C																																																																		
NPO (COJ)	Within ±120ppm/°C																																																																		
X7R	Within ±15%																																																																		
X5R	Within ±15%																																																																		
Y5V	Within +30%/-80%																																																																		
7.	Adhesive Strength of Termination	<ul style="list-style-type: none"> * Pressurizing force: 0201: 2N 0402 & 0603: 5N >0603: 10N * Test time: 10±1 sec. 	<ul style="list-style-type: none"> * No remarkable damage or removal of the terminations. 																																																																
8.	Vibration Resistance	<ul style="list-style-type: none"> * Vibration frequency: 10~55 Hz/min. * Total amplitude: 1.5mm * Test time: 6 hrs. (Two hrs each in three mutually perpendicular directions.) 	<ul style="list-style-type: none"> * No remarkable damage. * Cap change and Q/D.F.: To meet initial spec. 																																																																

Appendix I : Reliability Test Conditions and Requirements

NO.	Item	Test Condition	Requirements																																																										
9.	Solderability	<ul style="list-style-type: none"> * Solder temperature: 235±5°C * Dipping time: 2±0.5 sec. 	95% min. coverage of all metalized area.																																																										
10.	Bending Test	<ul style="list-style-type: none"> * The middle part of substrate shall be pressurized by means of the pressurizing rod at a rate of about 1 mm per second until the deflection becomes 1 mm and then the pressure shall be maintained for 5±1 sec. * Measurement to be made after keeping at room temp. for 24±2 hrs. 	<ul style="list-style-type: none"> * No remarkable damage. * Cap change: NPO: within ±5.0% or ±0.5pF whichever is larger. X7R, X5R: within ±12.5% Y5V: within ±30% (This capacitance change means the change of capacitance under specified flexure of substrate from the capacitance measured before the test.)																																																										
11.	Resistance to Soldering Heat	<ul style="list-style-type: none"> * Solder temperature: 270±5°C * Dipping time: 10±1 sec * Preheating: 120 to 150°C for 1 minute before immerse the capacitor in an eutectic solder. * Before initial measurement (Class II only): Perform 150+0/-10°C for 1 hr and then set for 48±4 hrs at room temp. * Measurement to be made after keeping at room temp. for 24±2 hrs. (Class I) or 48±4 hrs. (Class II). 	<ul style="list-style-type: none"> * No remarkable damage. * Cap change: NPO: within ±2.5% or ±0.25pF whichever is larger. X7R, X5R: within ±7.5% Y5V: within ±20% * Q/D.F., I.R. and dielectric strength: To meet initial requirements. * 25% max. leaching on each edge. 																																																										
12.	Temperature Cycle	<ul style="list-style-type: none"> * Conduct the five cycles according to the temperatures and time. <table border="1"> <thead> <tr> <th>Step</th> <th>Temp. (°C)</th> <th>Time (min.)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Min. operating temp. +0/-3</td> <td>30±3</td> </tr> <tr> <td>2</td> <td>Room temp.</td> <td>2-3</td> </tr> <tr> <td>3</td> <td>Max. operating temp. +3/-0</td> <td>30±3</td> </tr> <tr> <td>4</td> <td>Room temp.</td> <td>2-3</td> </tr> </tbody> </table> <ul style="list-style-type: none"> * Before initial measurement (Class II only): Perform 150+0/-10°C for 1 hr and then set for 48±4 hrs at room temp. * Measurement to be made after keeping at room temp. for 24±2 hrs. (Class I) or 48±4 hrs. (Class II). 	Step	Temp. (°C)	Time (min.)	1	Min. operating temp. +0/-3	30±3	2	Room temp.	2-3	3	Max. operating temp. +3/-0	30±3	4	Room temp.	2-3	<ul style="list-style-type: none"> * No remarkable damage. * Cap change: NPO: within ±2.5% or ±0.25pF whichever is larger. X7R, X5R: within ±7.5% Y5V: within ±20% * Q/D.F., I.R. and dielectric strength: To meet initial requirements. 																																											
Step	Temp. (°C)	Time (min.)																																																											
1	Min. operating temp. +0/-3	30±3																																																											
2	Room temp.	2-3																																																											
3	Max. operating temp. +3/-0	30±3																																																											
4	Room temp.	2-3																																																											
13.	Humidity (Steady State)	<ul style="list-style-type: none"> * Test temp.: 40±2°C * Humidity: 90~95% RH * Test time: 500+24/-0hrs. * Measurement to be made after keeping at room temp. for 24±2 hrs. (Class I) or 48±4 hrs. (Class II). 	<ul style="list-style-type: none"> * No remarkable damage. * Cap change: NPO: within ±5.0% or ±0.5pF whichever is larger. X7R, X5R: 10V, within ±12.5% 6.3V, within ±25% Y5V: within ±30% * Q/D.F. value: NPO: Cap 30pF, Q 350; 10pF Cap<30pF, Q 275+2.5C Cap<10pF; Q 200+10C X7R, X5R: <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>3.0%</td> <td>6.0%</td> <td>0603 0.047µF; 0805 0.18µF; 1206 0.47µF</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0805 1µF; 1210 10µF</td> </tr> <tr> <td>14.0%</td> <td>0603 0.33µF</td> </tr> <tr> <td rowspan="2">16V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF</td> </tr> <tr> <td>15.0%</td> <td>0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF, TT series & Cap 1µF</td> </tr> <tr> <td>6.3V</td> <td>15.0%</td> <td>30.0%</td> <td>0805 10µF; 1210 100µF</td> </tr> </tbody> </table> Y5V: <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>7.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>35V</td> <td>10.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">7.5%</td> <td>10.0%</td> <td>0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF</td> </tr> <tr> <td>12.5%</td> <td>0402 0.068µF</td> </tr> <tr> <td>16V (C<1.0µF)</td> <td>10.0%</td> <td>12.5%</td> <td>0402 0.068µF; 0603 0.68µF</td> </tr> <tr> <td>16V (C 1.0µF)</td> <td>12.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>10V</td> <td>15.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td>6.3V</td> <td>30.0%</td> <td>---</td> <td>---</td> </tr> </tbody> </table> <ul style="list-style-type: none"> * I.R.: 10V 1G or 50 -F whichever is smaller. 6.3V, 10 -F 	Rated vol.	D.F.	Exception of D.F.		50V	3.0%	6.0%	0603 0.047µF; 0805 0.18µF; 1206 0.47µF	25V	5.0%	10.0%	0805 1µF; 1210 10µF	14.0%	0603 0.33µF	16V	5.0%	10.0%	0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF	15.0%	0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF, TT series & Cap 1µF	6.3V	15.0%	30.0%	0805 10µF; 1210 100µF	Rated vol.	D.F.	Exception of D.F.		50V	7.5%	---	---	35V	10.0%	---	---	25V	7.5%	10.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF	12.5%	0402 0.068µF	16V (C<1.0µF)	10.0%	12.5%	0402 0.068µF; 0603 0.68µF	16V (C 1.0µF)	12.5%	---	---	10V	15.0%	---	---	6.3V	30.0%	---	---
Rated vol.	D.F.	Exception of D.F.																																																											
50V	3.0%	6.0%	0603 0.047µF; 0805 0.18µF; 1206 0.47µF																																																										
25V	5.0%	10.0%	0805 1µF; 1210 10µF																																																										
		14.0%	0603 0.33µF																																																										
16V	5.0%	10.0%	0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF																																																										
		15.0%	0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF, TT series & Cap 1µF																																																										
6.3V	15.0%	30.0%	0805 10µF; 1210 100µF																																																										
Rated vol.	D.F.	Exception of D.F.																																																											
50V	7.5%	---	---																																																										
35V	10.0%	---	---																																																										
25V	7.5%	10.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF																																																										
		12.5%	0402 0.068µF																																																										
16V (C<1.0µF)	10.0%	12.5%	0402 0.068µF; 0603 0.68µF																																																										
16V (C 1.0µF)	12.5%	---	---																																																										
10V	15.0%	---	---																																																										
6.3V	30.0%	---	---																																																										


Appendix I : Reliability Test Conditions and Requirements

NO.	Item	Test Condition	Requirements																																																										
14.	Humidity Load (Damp Heat)	<ul style="list-style-type: none"> * Test temp.: 40±2°C * Humidity: 90~95%RH * Test time: 500+24/-0 hrs. * To apply voltage: rated voltage (Max. 500V) * Measurement to be made after keeping at room temp. for 24±2 hrs. (Class I) or 48±4 hrs. (Class II). 	<ul style="list-style-type: none"> * No remarkable damage. * Cap change: NPO: within ±7.5% or ±0.75pF whichever is larger. X7R, X5R: 10V, within ±12.5% 6.3V, with ±25% Y5V: 10V, within ±30% 6.3V, within +30 to -40% * Q/D.F. value: NPO: Cap 30pF, Q 200; Cap<30pF, Q 100+10/3C X7R, X5R: <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>3.0%</td> <td>6.0%</td> <td>0603 0.047μF;0805 0.18μF;1206 0.47μF</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0805 1μF, 1210 10μF</td> </tr> <tr> <td>14.0%</td> <td>0603 0.33μF</td> </tr> <tr> <td rowspan="2">16V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0402 0.033μF; 0603 0.15μF; 0805 0.68μF; 1206 2.2μF</td> </tr> <tr> <td>15.0%</td> <td>0402 0.056μF; 0603 0.33μF; 0805 2.2μF; 1206 2.2μF, TT series & Cap 1μF</td> </tr> <tr> <td>6.3V</td> <td>15.0%</td> <td>30.0%</td> <td>0805 10μF;1210 100μF</td> </tr> </tbody> </table> <p>Y5V:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>7.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>35V</td> <td>10.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">7.5%</td> <td>10.0%</td> <td>0603 0.1μF; 0805 0.33μF; 1206 1μF; 1210 4.7μF</td> </tr> <tr> <td>12.5%</td> <td>0402 0.068μF</td> </tr> <tr> <td>16V (C<1.0μF)</td> <td>10.0%</td> <td>12.5%</td> <td>0402 0.068μF; 0603 0.68μF</td> </tr> <tr> <td>16V (C 1.0μF)</td> <td>12.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>10V</td> <td>15.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td>6.3V</td> <td>30.0%</td> <td>---</td> <td>---</td> </tr> </tbody> </table> <ul style="list-style-type: none"> * I.R.: 10V,500M or 25 -F whichever is smaller. 6.3V, 5 -F 	Rated vol.	D.F.	Exception of D.F.		50V	3.0%	6.0%	0603 0.047μF;0805 0.18μF;1206 0.47μF	25V	5.0%	10.0%	0805 1μF, 1210 10μF	14.0%	0603 0.33μF	16V	5.0%	10.0%	0402 0.033μF; 0603 0.15μF; 0805 0.68μF; 1206 2.2μF	15.0%	0402 0.056μF; 0603 0.33μF; 0805 2.2μF; 1206 2.2μF, TT series & Cap 1μF	6.3V	15.0%	30.0%	0805 10μF;1210 100μF	Rated vol.	D.F.	Exception of D.F.		50V	7.5%	---	---	35V	10.0%	---	---	25V	7.5%	10.0%	0603 0.1μF; 0805 0.33μF; 1206 1μF; 1210 4.7μF	12.5%	0402 0.068μF	16V (C<1.0μF)	10.0%	12.5%	0402 0.068μF; 0603 0.68μF	16V (C 1.0μF)	12.5%	---	---	10V	15.0%	---	---	6.3V	30.0%	---	---
Rated vol.	D.F.	Exception of D.F.																																																											
50V	3.0%	6.0%	0603 0.047μF;0805 0.18μF;1206 0.47μF																																																										
25V	5.0%	10.0%	0805 1μF, 1210 10μF																																																										
		14.0%	0603 0.33μF																																																										
16V	5.0%	10.0%	0402 0.033μF; 0603 0.15μF; 0805 0.68μF; 1206 2.2μF																																																										
		15.0%	0402 0.056μF; 0603 0.33μF; 0805 2.2μF; 1206 2.2μF, TT series & Cap 1μF																																																										
6.3V	15.0%	30.0%	0805 10μF;1210 100μF																																																										
Rated vol.	D.F.	Exception of D.F.																																																											
50V	7.5%	---	---																																																										
35V	10.0%	---	---																																																										
25V	7.5%	10.0%	0603 0.1μF; 0805 0.33μF; 1206 1μF; 1210 4.7μF																																																										
		12.5%	0402 0.068μF																																																										
16V (C<1.0μF)	10.0%	12.5%	0402 0.068μF; 0603 0.68μF																																																										
16V (C 1.0μF)	12.5%	---	---																																																										
10V	15.0%	---	---																																																										
6.3V	30.0%	---	---																																																										
15.	High Temperature Load (Endurance)	<ul style="list-style-type: none"> * Test temp.: NPO, X7R: 125±3°C X5R, Y5V: 85±3°C * To apply voltage: (1) 6.3V or C 10μF (for X7R, X5R): 150% of rated voltage. (2) 6.3V<V<500V and C<10μF (for X7R, X5R): 200% of rated voltage. (3) 500V: 150% of rated voltage. (4) V 630V: 120% of rated voltage. (Max. 3600V) * Test time: 1000+24/-0 hrs. * Measurement to be made after keeping at room temp. for 24±2 hrs. (Class I) or 48±4 hrs. (Class II). 	<ul style="list-style-type: none"> * No remarkable damage. * Cap change: NPO: within ±3.0% or ±0.3pF whichever is larger. X7R, X5R: 10V, within ±12.5% 6.3V, with ±25% Y5V: 10V, within ±30% 6.3V, within +30 to -40% * Q/D.F. value: NPO: Cap 30pF, Q 350 10pF Cap<30pF, Q 275+2.5C Cap<10pF, Q 200+10C X7R, X5R: <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>3.0%</td> <td>6.0%</td> <td>0603 0.047μF; 0805 0.18μF, 1206 0.47μF</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0805 1μF, 1210 10μF</td> </tr> <tr> <td>14.0%</td> <td>0603 0.33μF</td> </tr> <tr> <td rowspan="2">16V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0402 0.033μF; 0603 0.15μF; 0805 0.68μF; 1206 2.2μF</td> </tr> <tr> <td>15.0%</td> <td>0402 0.056μF; 0603 0.33μF; 0805 2.2μF; 1206 2.2μF TT series & Cap 1μF</td> </tr> <tr> <td>6.3V</td> <td>15.0%</td> <td>30.0%</td> <td>0805 10μF; 1210 100μF</td> </tr> </tbody> </table> <p>Y5V:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>7.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>35V</td> <td>10.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">7.5%</td> <td>10.0%</td> <td>0603 0.1μF; 0805 0.33μF; 1206 1μF; 1210 4.7μF</td> </tr> <tr> <td>12.5%</td> <td>0402 0.068μF</td> </tr> <tr> <td>16V (C<1.0μF)</td> <td>10.0%</td> <td>12.5%</td> <td>0402 0.068μF; 0603 0.68μF</td> </tr> <tr> <td>16V (C 1.0μF)</td> <td>12.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>10V</td> <td>15.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td>6.3V</td> <td>30.0%</td> <td>---</td> <td>---</td> </tr> </tbody> </table> <ul style="list-style-type: none"> * I.R.: 10V,1G or 50 -F whichever is smaller. 6.3V, 10 -F 	Rated vol.	D.F.	Exception of D.F.		50V	3.0%	6.0%	0603 0.047μF; 0805 0.18μF, 1206 0.47μF	25V	5.0%	10.0%	0805 1μF, 1210 10μF	14.0%	0603 0.33μF	16V	5.0%	10.0%	0402 0.033μF; 0603 0.15μF; 0805 0.68μF; 1206 2.2μF	15.0%	0402 0.056μF; 0603 0.33μF; 0805 2.2μF; 1206 2.2μF TT series & Cap 1μF	6.3V	15.0%	30.0%	0805 10μF; 1210 100μF	Rated vol.	D.F.	Exception of D.F.		50V	7.5%	---	---	35V	10.0%	---	---	25V	7.5%	10.0%	0603 0.1μF; 0805 0.33μF; 1206 1μF; 1210 4.7μF	12.5%	0402 0.068μF	16V (C<1.0μF)	10.0%	12.5%	0402 0.068μF; 0603 0.68μF	16V (C 1.0μF)	12.5%	---	---	10V	15.0%	---	---	6.3V	30.0%	---	---
Rated vol.	D.F.	Exception of D.F.																																																											
50V	3.0%	6.0%	0603 0.047μF; 0805 0.18μF, 1206 0.47μF																																																										
25V	5.0%	10.0%	0805 1μF, 1210 10μF																																																										
		14.0%	0603 0.33μF																																																										
16V	5.0%	10.0%	0402 0.033μF; 0603 0.15μF; 0805 0.68μF; 1206 2.2μF																																																										
		15.0%	0402 0.056μF; 0603 0.33μF; 0805 2.2μF; 1206 2.2μF TT series & Cap 1μF																																																										
6.3V	15.0%	30.0%	0805 10μF; 1210 100μF																																																										
Rated vol.	D.F.	Exception of D.F.																																																											
50V	7.5%	---	---																																																										
35V	10.0%	---	---																																																										
25V	7.5%	10.0%	0603 0.1μF; 0805 0.33μF; 1206 1μF; 1210 4.7μF																																																										
		12.5%	0402 0.068μF																																																										
16V (C<1.0μF)	10.0%	12.5%	0402 0.068μF; 0603 0.68μF																																																										
16V (C 1.0μF)	12.5%	---	---																																																										
10V	15.0%	---	---																																																										
6.3V	30.0%	---	---																																																										

Appendix II : General Information

Construction

No.	Name	NP0/X7R	X7R/X5R/Y5V
①	Ceramic material	BaTiO ₃ based	
②	Inner electrode	AgPd alloy	Ni
③	Termination	Inner layer	Ag
④		Middle layer	Ni
⑤		Outer layer	Sn (Matt)



Storage and handling conditions

- (1) To store products at 5 to 40°C ambient temperature and 20 to 70% related humidity conditions.
- (2) The product is recommended to be used within one year after shipment. Check solderability in case of shelf life extension is needed.

Cautions:

- Don't store products in a corrosive environment such as sulfide, chloride gas, or acid. It may cause oxidization of electrode, which easily be resulted in poor soldering.
- To store products on the shelf and avoid exposure to moisture.
- Don't expose products to excessive shock, vibration, direct sunlight and so on.

Recommended soldering conditions

The lead-free termination MLCCs are not only to be used on SMT against lead-free solder paste, but also suitable against lead-containing solder paste. If the optimized solder joint is requested, increasing soldering time, temperature and concentration of N₂ within oven are recommended.

